
DECAL beam test at CERN

Paul Dauncey


for the CALICE-UK/SPiDeR groups:

Birmingham, Bristol, Imperial, Oxford, RAL

Digital ECAL

- Concept is to count particles, not deposited energy

- Use very small pixels ($\sim 50\mu\text{m}$) with binary readout
- In principle removes Landau fluctuations so giving better ECAL resolution
- Very small pixels should also help with PFA
- Need very large number of pixels $\sim 10^{12}$ for ILC ECAL




- Basic studies and proof of principle required
 - DECAL never been operated for real
 - Sensitive to core density of EM showers; not measured at high granularity

SPiDeR collaboration

- ILC work announced to be cut by UK funding agencies Dec 2007
 - CALICE-UK closed down by Mar 2009; UK still members of CALICE but no specific UK funding for CALICE activities
 - Same happened to UK vertex group, LCFI
- Regroup in the UK to form new collaboration, SPiDeR
 - Silicon Pixel Detector R&D
 - Remnants of CALICE-UK DECAL group and LCFI
 - “Generic” pixel detectors for future colliders...
 - ...which just so happen to be very ILC-like ☺
- SPiDeR in principle is approved and funded for three year program
 - Part of which is to build a DECAL physics prototype calorimeter
 - But UK funding still in a mess; currently on temporary funds for one year
 - Will find out at end of 2009 if full funding will be given from Apr 2010



TPAC sensor

- Tera-Pixel Active Calorimeter
 - 0.18 μm CMOS process
 - 168 \times 168 pixels, each 50 \times 50 μm^2 , total of 28k pixels
 - Active area 0.84 \times 0.84 cm^2
 - Per pixel trim and masking
 - Binary readout with common sensor threshold
 - No external readout chip needed
 - On-sensor memory storage
- Sensor operates in ILC-like mode
 - Sensitive for “bunch train” period, consisting of many “bunch crossings” (BX)
 - Readout must be completed before next bunch train



TPAC sensor on PCB

- $1 \times 1 \text{ cm}^2$ TPAC sensor



CERN beam test

- Beam test at CERN 13-27 August
 - Main aim was to measure pixel efficiency for MIPs
 - Not possible to measure EM resolution; sensors too small to contain showers as size $<$ Molière radius
- Ran parasitically for two weeks
 - Behind two other primary users both using the EUDET tracking telescope
 - First week; Fortis pixel sensors (connected with SPiDeR so effectively collaborators but the two systems ran independently)
 - Second week; SiLC strip sensors
 - Back in the same old H6B beam line as used by CALICE in 2006/07
- Six sensors in a stack
 - 170k pixels total
 - No tungsten within stack; run as six-layer tracker
 - Track interpolation should allow efficiency measurement

DECAL stack in H6B



Placed exactly where
CALICE SiECAL/AHCAL
used to be



$1 \times 1 \text{ cm}^2$ scintillators
mounted at front


DECAL readout



Side view showing six layers





Readout via USB;
no VME crates



Fake bunch train operation

- ILC-like; no trigger...
 - Sensor needs to operate with bunch trains
 - Pre-bunch train reset period needed; cannot start train when trigger seen
 - Operator by generating fake bunch trains and hope some beam particles arrive during the train
- ...but not very ILC-like!
 - To get rate up, needed to push all parameters beyond ILC
 - Bunch train = 8000BX (not ~2000BX)
 - 1 BX = 400ns (not ~300ns) so bunch train = 3.2ms (not ~1ms)
- Longer bunch trains/crossings give more particles per train but
 - More noise hits per BX and per train
 - Memory more likely to saturate; inefficiency
 - Masked noisiest pixels to reduce rate; trade-off for efficiency
 - Need to take out these effects in analysis to see “real” pixel efficiency

Bunch train rates and total




Scintillator/PMT timing

- Three **scintillators** installed
 - Two in front, one behind the TPAC stack
- Used to **tag time** of particles within bunch train
 - PMT outputs discriminated, latched and read out per BX
- Use **PMT coincidence** to define BX of particle
 - Coincidence count gives number of particles
 - Look for sensor hits with fixed BX offset from particle
 - Offset allows for timing differences in two systems (including epitaxial charge drift time)

Spill structure


- **Typical** run: even single hit rate shows **beam spill structure**

Pmt0




Spill structure

- Zoom in to see detail



Spill structure


- Zoom in to see detail



- Duty cycle $\sim 25\%$ (maximum, assuming no beam loss)
- Some runs had 49sec spill period rather than 40sec; $\sim 20\%$



Scintillator/PMT rates

- **Fit** number of coincidences per bunch train
 - Poisson distribution for number of particles
 - Zero for bunch trains outside of spill





Scintillator/PMT rates vs run number

- Check duty cycle and Poisson mean per bunch train
 - Poisson mean of 0.32 during the 3.2ms bunch train is equivalent to **100Hz** beam rate on scintillators



- Max rate seen was **~250Hz**; was hoping for $>1\text{kHz}$


Scintillator coincidence rates to disk



- Total sample $\sim 1.4\text{M}$ time-tagged particles


Sensor hits relative to PMT coincidence

- Typical run 447790, layer 0



Sensor hits relative to PMT coincidence



- Typical run 447790, layer 0



- Use PMT coincidence BX offset in time by 4000BX for **background** level, i.e. $t_b = (t_s + 4000) \% 8000$

Particle correlations in sensors

- Beam particles ~parallel to z axis
 - Strong **correlation** layer to layer in sensor hit positions




- Layers 0 back-facing, layer 1 front-facing so local x is anti-correlated

Track χ^2 probability

- Use correlations to pick hits for tracks and alignment


Chi-squared probability of x fit



- χ^2 probability reasonably flat; indicates fit is sensible


Alignment Δx vs time

- Typical layer 3



Alignment vs time


- Typical layer 3




Got lucky on the last day

- SiLC group finished data-taking one day before schedule
 - After they packed up, we could control beam
- Swapped to running with electrons
 - Five energies; 20, 40, 60, 80, 100GeV
- Before end of pion runs, put 30mm of tungsten in front of stack
 - Corresponds to $8.6X_0$ or 0.31 interaction lengths
 - Around $\frac{1}{4}$ of pions should interact
- Electron runs
 - Should give first data on EM shower core density
 - Must do comparison with MC
 - Must understand sensor hit efficiency first

Tungsten converter with pions



Tungsten converter with electrons



Next steps

- Do analysis of efficiency measurement from these data
 - Basic property of the sensor
- Must do detailed comparison with MC to understand EM shower core densities
 - Core density sets main requirement for pixel size (and hence pixel count, power, etc)
 - Probably need more electron data so bid for beam time at DESY, most likely early 2010
- Assuming three years funding really appears in April 2010
 - Build DECAL physics prototype by ~2012
 - 20-30 layers (depending on funding)
 - Should allow full EM shower containment
 - Proof-of-principle of DECAL concept

Conclusions

- Data from the DECAL CERN beam test look **good**
- Scintillators/PMTs give a good **time tag** for particles
- Sensors were **mechanically stable** when not touched but moved significantly during handling of the stack
- **Efficiency** for sensors is critical measurement
 - Affected by non-ILC operation
 - Will have many effects contributing
 - Need full **tracking analysis** to untangle
- Some **EM shower data** to start shower density studies